


## Distributors with adjustable restrictors

VU27/1



This system makes it easy to adjust the flow to each point.  
Regular checks are needed to anticipate cloggings in fine adjustments. It is recommended to assemble a filter to the supply point.

### Technical characteristics

Max. flow per outlet..... 2-4 l/min (according to size)  
Temperature..... -30°C ÷ +80°C  
Maximum pressure..... 15 bar

### Dimensions

VU27/10  
- up to 2 l/min -

E	S
G 1/4	G 1/8

H	H1	L1	L2
30	20	19	17

	L	L3	L4
1 outlet	38	21	8,5
2 outlets	55	-	27,5
3 outlets	72	17	27,5
4 outlets	89	34	27,5
5 outlets	106	51	27,5
6 outlets	123	68	27,5
7 outlets	140	85	27,5
8 outlets	157	102	27,5

VU27/11  
- up to 4 l/min -

E	S
G 3/8	G 1/4

H	H1	L1	L2
40	30	25	25

	L	L3	L4
3 outlets	100	25	37,5
4 outlets	125	50	37,5
5 outlets	150	75	37,5
6 outlets	175	100	37,5

271 X X 0000

Size	X	Number of outlets	X
Up to 2 l/min	0	1 to 8	1...8
Up to 4 l/min	1	3 to 6	3...6

